speco technologies®
simply unique

# Intense-IR Series Color Day/Night Indoor Dome Cameras

| | |
|---|---|
| CVC5725DNV | 4 - 9mm auto iris varifocal lens, black housing |
| CVC5725DNVW | 4 - 9mm auto iris varifocal lens, white housing |
| CVC5825DNV | 2.8 - 12mm auto iris varifocal lens, black housing |
| CVC5825DNVW | 2.8 - 12mm auto iris varifocal lens, white housing |
| CVC5925DNV | 9 - 22mm auto iris varifocal lens, black housing |
| CVC5925DNVW | 9 - 22mm auto iris varifocal lens, white housing |




## Features

- 1/3” Sony Super-HAD II™ CCD
- 3D-DNR (Sense-up) - sharp image under ultra low light level
- Intense-IR function - no saturation image, vivid image
- Defect function - elimination of white spots
- HSBLC (High Light Suppression BLC)
- Privacy zone
- Third-Generation DSP chip
- ICR - removable IR cut filter
- Convenient On-Screen Display (OSD) function controls
- 12VDC / 24VAC dual voltage operation
- 5 year warranty

## Specifications

| | |
|---|---|
| Image Sensor | 1/3” Sony Super-HAD II™ CCD |
| Resolution | 600 TV lines |
| Minimum Illumination | 0.000006 lux (IR LEDs on) |
| Total Pixels | 811 (H) x 508 (V) |
| Number of LEDs | 33 |
| IR Range | Up To 65’ |
| White Balance | ATW / AWB / Manual / AWC - Set |
| Gain Control | High / Middle / Low / Off |
| S/N Ratio | 52dB (AGC off, Weight on) |
| Backlight Compensation | BLC / HSBLC / Off |
| Effective Pixels | 768 (H) x 494 (V) |
| Electronic Shutter Speed | Auto (1/50, 1/60 sec. - 1/100,000 sec.) |
| OSD | Built-In |
| 3 DNR | On / Off (0-100 levels adjustable) |
| D-WDR | Indoor / Outdoor / Off |
| Sharpness | 0-31’ (level adjustable) |
| Privacy | On / Off (8 zones) |
| Scanning System | 2:1 interlace |
| Synchronization | Internal / Line-Lock |
| Motion Detection | On / Off (4 zones) |
| Sense-Up | Off / Auto (selectable limit x2 - x256) |
| Mirror | Off / Mirror / V-Rev / Rotate |
| Freeze | On / Off |
| Day & Night | Color / BW / Auto / EXT |
| Digital Zoom: | On (32x) / Off |
| Blemish Compensation | Auto: 128 point / Manual: 4 point |
| Power Supply | 12VDC / 24VAC (dual voltage) (power supply not included) |
| Power Consumption | 12VDC, 250mA (CDS off)<br>12VDC, 700mA (CDS on)<br>24VAC, 100mA (CDS off)<br>24VAC, 250mA (CDS on) |
| Operating Temperature/ Humidity | 14˚ F - 122˚ F / RH 95% max. |
| Storage Temperature/ Humidity | -4˚ F - 140˚ F / RH 95% max. |
| Dimensions | 4.8” (W) x 4” (H) x 4.8” (Dia.) |
| Weight | 1.2 lbs. |

## Optional Accessories

CVCWM
Corner Mount

PSW4
Power Supply

PSW5
Power Supply

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 1/17/12

For more information contact Speco Technologies
200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com